



CipherLab 2200 Omnidirectional Scanner for Fast and Reliable Workflow

Category

Omnidirectional Scanner for
Fast and Reliable Workflow

Optical Sensor

CMOS Image Sensor
1280x800 pixels

Light source

LED RED 620 nm

Resolution

1D - 3mil / PDF417 - 5mil / 2D - 7mil

Barcode support

Code 39.3 mil: 0 to 5 cm / 0 to 2 in
QR Code mil: 0.5 to 2.5cm / 0.2 to 1.0
in EAN13 13mil: 0 to 20 cm / 0 to 7.9
in PDF417 5mil 1 to 6 cm / 0.4 to 2.4
in

Pitch, Skew

± 70°, ± 75°

Print Contrast (Minimum)

25%

Ambient Illumination

100,000 Lux

Hands-free scanning

Presentation mode

Language support

US and UK English

Color

Black

Barcode support

1D: Codabar, Code 39, Code 93,
Code 128, GS1 DataBar (RSS),

Industrial 2 of 5, Interleave 2 of 5,
ISBT-128, Italian and French

Pharmacodes, Matrix 2 of 5, MSI,
Plessey, Telepen,

UPC/EAN/GS1-128, Code 11

2D: PDF417, MicroPDF417, Data
Matrix, QR code, Micro QR

Code, Aztec, MaxiCode,
Composite Codes

Dimension LxWxH(mm)

80 x 83 x 150 mm / 3.2 x 3.3 x 5.9 in

Weight

320g / 11 oz.

Trigger

1 trigger for handheld operation
30 mA / 600 mA

Indicators

Magnetic Buzzer (Adjustable Tone
and Volume), Good Read LED

Input Voltage

5V 2A Max

Power consumption¹

Standby / Operating
300mA / 450mA

Accessories

RS232 cable
Power Supply